



HYDROTAP G5 BCSHA20 CELSIUS ALL-IN-ONE ARC CHROME

 **BOILING**

 **CHILLED**

 **SPARKLING**

 **HOT & AMBIENT**

FILTERED

UNFILTERED

Order Code H57760Z00AU

Zip HydroTap Design Range CELSIUS All-In-One Boiling, Chilled & Sparkling Filtered water, plus Hot and Cold washing up water from a single tap (hot and cold water supply required). The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and a refillable CO2 cylinder. Easy to install integrated ventilation tray included.



Manufacturing Code	H57760Z00AU
Capacity	Commercial
Boiling Cups per hour	100
Combined Chilled and Sparkling Cups per hour	75

Tap	Zip HydroTap Design Range CELSIUS All-In-One ARC Tap (Chrome)
Water Pressure	Min 250kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold and Hot

Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.96kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W339mm x D460mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	5 Star, 6.0 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

Ventilation requirements Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

200
333
50
Command Centre width

Air outlet louvre (if required)
Cut-out in door/wall, towards the top of the cabinet

Air inlet cut-out (required)
Cut-out in cabinet floor

max. 43
285
326

HydroTap Tap options

Celsius All-in-One Arc Tap

Classic Plus All-in-One Tap

Classic All-in-One Tap

Tap Positioning
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot.

Ø50mm hole for Tap

Sink

Celsius All-in-One Arc Tap

Clearance Envelope

4mm buffer pad air space

Clearance Envelope

460

Mains cold water isolation valve (not supplied)

Air inlet grille

IEC Flex & Plug 230-240V, 50Hz power outlet

CO₂ gas cylinder Ø140

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

Mains hot water supply installation
Hot and cold water supply required

50mm hole in sink/benchtop for All-in-One tap

RED marked braided hose to mixer tap

Hot water isolation valve (not supplied)

BLUE marked braided hose

Braided hose to HydroTap Command Centre MAINS Inlet

Mains water isolation valve (not supplied)

HydroTap G5
BCS20

shown with Celsius All-in-One Arc Tap

Tap Detail

