

## KDIAM90AX

Integrated hood, Universale, Stainless steel, 90 cm



### TYPE

Product family: Hood • Hood Type: Integrated hood • Hood width: 90 cm • Extraction: Extraction • Electronic control: Yes • EAN code: 8017709217082

### AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Universale • Design: Fully integrated • Material: Stainless steel • Type of steel: Brushed

### PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

### CONTROLS

Control setting: Electronic buttons • Led color: White

## TECHNICAL FEATURES

No. of lights: 4 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 1400 m<sup>3</sup>/h • Motor power: 550 W • No. of filters: 2 • Anti-grease filters: Buffle • Filter replacement indicator: Yes • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

### ELECTRICAL CONNECTION

Electrical connection rating: 555 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

### OPTIONAL ACCESSORIES

#### SPEED 1

Extraction rate IEC 61591: 552 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 46 dB(A) • Power: 154 W

#### SPEED 2

Extraction rate IEC 61591: 950 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 63 dB(A) • Power: 255 W

#### SPEED 3

Extraction rate IEC 61591: 1412 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 71 dB(A) • Power: 334 W

#### SPEED 4

### INTENSIVE SPEED

Extraction rate (IEC 61591): 1555 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 74 dB(A) • Power: 370 W

### LOGISTIC INFORMATION

Dimensions of the product (mm): 315x900x295 • Width: 900 mm • Depth (mm): 295 mm • Product Height (mm): 315 mm • Net weight (kg): 19.800 kg • Gross weight (kg): 22.680 kg



