
DBR9980HB
DBR9989HB
DBR9982HB

**EN** User manual
Cooker Hood

## Enjoy peace of mind. Register your appliance today.

Stay updated on better living services, safety notices and shop for accessories.


1. **Open the camera app on your smartphone and point at the QR code to scan.**
   Product Registration QR code is located on the front or underside of your appliance.



2. **Tap the notification or link to open the registration form.**

3. **Complete your details and enjoy peace of mind.**

# USER MANUAL



AEG

# CONTENTS

**1.** SAFETY INFORMATION .....3
**2.** USE .....8
**3.** CARE AND CLEANING .....9
**4.** CONTROLS .....10
**5.** LIGHTING .....10

# FOR PERFECT RESULTS

Thank you for choosing this AEG product. We have created it to give you impeccable performance for many years, with innovative technologies that help make life simpler – features you might not find on ordinary appliances. Please spend a few minutes reading to get the very best from it.

**Visit our website for:**

Get usage advice, brochures, trouble shooter, service information:
**www.aeg.com**

Register your product for better service:
**www.registeraeg.com**

Buy Accessories, Consumables and Original spare parts for your appliance:
**www.aeg.com/shop**

# CUSTOMER CARE AND SERVICE

Always use original spare parts.
When contacting our Authorised Service Centre, ensure that you have the following data available: Model, PNC, Serial Number.
The information can be found on the rating plate.

Warning / Caution-Safety information
General information and tips
Environmental information

Subject to change without notice.

# 1.SAFETY INFORMATION

ⓘ For your safety and correct operation of the appliance, read this manual carefully before installation and use. Always keep these instructions with the appliance even if you move or sell it. Users must fully know the operation and safety features of the appliance.

⚠ The wire connection has to be done by specialized technician.

⚠ The motor earth connection shall be performed before the connections of the neutral and phase conductors. In case of replacement, the neutral and phase connections shall be disconnected before the earth connection.

⚠ The installation of the hood and the remote motor must be carried out by specialized personnel.

- The manufacturer will not be held liable for any damages resulting from incorrect or improper installation.
- The minimum safety distance between the cooker top and the extractor hood is 650 mm (some models can be installed at a lower height, please refer to the paragraphs on working dimensions and installation).
- If the instructions for installation for the gas hob specify a greater distance, this must be respected.
- Check that the mains voltage corresponds to that indicated on the rating plate fixed to the inside of the hood.
- Means for disconnection must be incorporated in the fixed wiring in accordance with the wiring rules.
- For Class I appliances, check that the domestic power supply guarantees adequate earthing.
- Connect the extractor to the exhaust flue through a pipe of minimum diameter 150 mm. The route of the flue must be as short as possible.
- Regulations concerning the discharge of air have to be fulfilled.
- Do not connect the extractor hood to exhaust ducts carrying combustion fumes (boilers, fireplaces, etc.).
- If the extractor is used in conjunction with non-electrical

appliances (e.g. gas burning appliances), a sufficient degree of aeration must be guaranteed in the room in order to prevent the backflow of exhaust gas. When the cooker hood is used in conjunction with appliances supplied with energy other than electric, the negative pressure in the room must not exceed 0,04 mbar to prevent fumes being drawn back into the room by the cooker hood.

- The air must not be discharged into a flue that is used for exhausting fumes from appliances burning gas or other fuels.
- If the supply cord is damaged, it must be replaced from the manufacturer or its service agent.
- Connect the plug to a socket complying with current regulations, located in an accessible place.
- With regards to the technical and safety measures to be adopted for fume discharging it is important to closely follow the regulations provided by the local authorities.

⚠ **WARNING:** Before installing the Hood, remove the protective films.

- Use only screws and small parts in support of the hood.

⚠ **WARNING:** Failure to install the screws or fixing device in accordance with these instructions may result in electrical hazards.

- Do not look directly at the light through optical devices (binoculars, magnifying glasses…).
- Do not flambè under the range hood; risk of fire.
- This appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved. Children shall not play with the appliance. Cleaning and user maintenance shall not be made by children without supervision.
- Children should be supervised to ensure that they do not play with the appliance.
- The appliance is not to be used by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they

have been given supervision or instruction.

⚠ Accessible parts may become hot when used with cooking appliances.

- Clean and/or replace the Filters after the specified time period (Fire hazard). See paragraph Care and Cleaning.
- There shall be adequate ventilation of the room when the range hood is used at the same time as appliances burning gas or other fuels (not applicable to appliances that only discharge the air back into the room).
- Range hoods and other cooking fume extractors may adversely affect the safe operation of appliances burning gas or other fuel( including those in other rooms ) due to back flow of combustion gases. These gases can potentially result in carbon monoxide poisoning. After installation of a range hood or other cooking fume extractor, the operation of flued gas appliances should be tested by a competent person to ensure that back flow of combustion gases does not occur.
- The symbol ⍰ on the product or on its packaging indicates that this product may not be treated as household waste. Instead it shall be handed over to the applicable collection point for the recycling of electrical and electronic equipment. By ensuring this product is disposed of correctly, you will help prevent potential negative consequences for the environment and human health, which could otherwise be caused by inappropriate waste handling of this product. For more detailed information about recycling of this product, please contact your local city office, your household waste disposal service or the shop where you purchased the product.

- Select a location which avoids causing a nuisance to neighbours from noise and air emissions from device.
- Be aware of local council rules regarding maximum allowable noise levels.

**⚠ WARNING:**

- Ensure the rangehood is switched off before carrying out maintenance, to avoid any possibility of electric shock.
- This rangehood is not recommended for barbecues.
- Exhaust air must not be discharged into a wall cavity, unless the cavity is designed for the purpose.
- Always cover lit gas burners with pots or pans when the rangehood is in use.
- Always switch off gas burners before you remove pots or pans.

**⚠ CAUTION:**

- In order to avoid a hazard due to inadvertent resetting of the thermal cut-out, this appliance must not be supplied through an external switching device, such as a timer, or connected to a circuit that is regularly switched on and off by the utility.

## ELECTRICAL CONNECTION

- Check that the installation complies with standards of local gas and electricity authorities.
- If the supply cord is damaged, it must be replaced by the manufacturer or its service agent or a similarly qualified person in order to avoid a hazard.
- Ensure that the plug is accessible after installation.

## ACCESSORIES

- When using flexible duct always install duct with the wire helix pulled taut to minimise pressure loss.
- Try to keep exhaust duct short and straight.
- Keep bends in the exhaust duct to a minimum.
- Do not restrict exhaust duct.
- Reducing the size of the exhaust duct will reduce the airflow of the rangehood. Please read instructions carefully. Service calls resulting from incorrect installation will be charged for.

- Installation must comply in all respects with your gas and electrical authorities. This rangehood is an indoor domestic appliance, and has been manufactured and tested to comply with Australian and New Zealand Standard AS/NZS 60335.2.31

# 2.USE

- The extractor hood has been designed exclusively for domestic use to eliminate kitchen smells.
- Never use the hood for purposes other than for which it has been designed.
- Never leave high naked flames under the hood when it is in operation.
- Adjust the flame intensity to direct it onto the bottom of the pan only, making sure that it does not engulf the sides.
- Deep fat fryers must be continuously monitored during use: overheated oil can burst into flames.
- Always switch off gas burners before removing pots or pans.

**Condensation on rangehood surfaces**

**In some applications customers using induction cooktops may experience condensation forming on surfaces of the rangehood.**

**Some conditions may contribute to the formation of condensation such as;**


- **Room temperature and humidity.**
- **Installation height of rangehood above the cooktop.**
- **Size and type of cookware used.**
- **How the induction cooktop is used.**
- **Incorrect flue diameter (i.e. too small), flue length too long, too many bends in flue.**

**Some methods to reduce the occurrence of condensation are;**

1. **Use the right speed according to the type of cooking;**
   **a. Speed 1: light frying/boiling.**
   **b. Speed 2: frying/wok cooking/ heavy boiling.**
   **c. Speed 3: grilling, intensive frying and wok cooking.**
2. **Before you start cooking, switch on the range hood at minimum speed, to control moisture and remove cooking odour;**
3. **Increase the range hood speed only when the amount of vapor makes it necessary; (i.e., increase fan speed as more steam is generated).**
4. **Use boost speed only when it is strictly necessary.**
5. **Use pot lid when boiling to control moisture.**
6. **If the cooking zones of the induction cooker allows, choose the smallest pot practicable for cooking.**
7. **Keep range hood filter(s) clean to optimize grease and odour efficiency.**


# 3.CARE AND CLEANING

- The Grease filters must be cleaned every 2 months of operation, or more frequently for particularly heavy usage, and can be washed in a dishwasher.



- Clean the hood using a damp cloth and a neutral liquid detergent.
- Wipe the rangehood body and flue with a sponge or soft cloth soaked in warm soapy water, and dry with a soft cloth, for stainless steel models apply a stainless steel protector. Do not use oven cleaners or other abrasive materials.
- There is a fire risk if cleaning is not carried out in accordance with instructions.

# 4.CONTROLS




| Button | Function | Led |
|---|---|---|
| A | Turns off the motor. | - |
| | Press and hold the button for approximately 2 seconds, with all the loads turned off (Motor+Lights), to reset the Filter saturation alarm. All led flashes three times. | Flashing. |
| | With the motor turned off:<br>Saturation of the grease filters takes place after 100 hours of continuous operation of the hood. | Flashes once a second. |
| B | Turns the Motor on at speed 1. | On. |
| C | Turns the Motor on at speed 2. | On. |
| | Press and hold the button for 2 seconds to activate Delay Off function for speed 1, 2 and 3.<br>After 6 minutes the fan will automatically turn off. | Flashes once a seconds. |
| D | Turns the Motor on at speed 3. | On. |
| | Press and hold for 2 seconds to activate Intensive Boost speed. After 6 minutes, the motor will automatically return to the speed that the hood was previously set to.<br>To deactivate it, press button D once more or press button A. | Flashes once every 0.5 seconds. |
| E | Press briefly: Turns the lighting system on and off at maximum intensity. | On. |
| | Press and hold to change the lighting intensity up or down. | - |

# 5.LIGHTING

- For replacement contact technical support (“To purchase contact technical support”).

www.aeg.com/shop



991.0697.455_02 - 251110
D00009186_01

CE

AEG